




CANTILEVER RACKING

QUOTE REQUEST FORM

WHAT STRENGTH DO YOU REQUIRE?

- Light Duty
 Medium Duty
 If unsure, please advise below how much weight you require each arm to hold

HOW MANY RUNS & HOW MANY BAYS PER RUN? *example: 2 runs of 3 bays =*



SINGLE SIDED OR DOUBLE SIDED?

- Single Sided
 Double Sided

POST HEIGHT?

• LIGHT DUTY

- 2000mm
 2400mm
 3000mm
 3600mm
 4200mm
Not available in HDG

• MEDIUM DUTY

- 2438mm
 3048mm
 3658mm
 4267mm
 4877mm
 6096mm
Not available in P/C

POST CENTRES?

- 900mm
 1200mm
 1500mm
 1800mm
 2100mm

Not available in Light Duty
Not available in HDG

ARM LENGTH?

- 700mm
 900mm
 1200mm
 1500mm
Not available in Medium Duty Not available in Light Duty

HOW MANY ARM LEVELS PER POST?

INSTALL SUBURB & POSTCODE?

PICK UP OR DELIVERY?

- Pick up
 Delivery

DELIVERY ADDRESS (IF APPLICABLE)

DO YOU HAVE A FORKLIFT ON SITE TO UNLOAD? (IF APPLICABLE)

- Yes
 No

(please continue onto next page)

SAFETY

XPRESS
.com.au



CANTILEVER RACKING

QUOTE REQUEST FORM

PLEASE ONLY ANSWER THE BELOW QUESTIONS IF THE RACK WILL BE INSTALLED OUTDOORS

SUBURB & POSTCODE OF INSTALL LOCATION:

(Feel free to share the install location via Google Maps)

IS INSTALL LOCATION IN AN INDUSTRIAL COMPLEX/ESTATE?

Yes No

HOW FAR AWAY ARE THE NEAREST TWO 5mH OR HIGHER BUILDINGS?

- Racking to be installed no more than 5m from buildings in a well-developed industrial area.
- Racking to be installed no more than 100m from buildings in a well-developed industrial area or no more than 50m from buildings in a semi-built up area.
- Racking to be installed no more than 200m from buildings in a rural area containing trees.
- Racking to be installed where there is no buildings, development or trees within 200m (flat plane or field).



CANTILEVER RACKING

QUOTE REQUEST FORM

NOTES / SKETCHES / PLANS

Grid area for notes, sketches, or plans.